



North America's #1 Manufacturer
of High-Quality Cleaning Equipment

MODEL 555SS Hot-Water Pressure Washer

Electric / Direct Drive

Hose reel (optional) makes hose mobility and storage easy and convenient. Also keeps work areas neat and safe while protecting hoses from damage



Heater coils carry a 5-year warranty

Convenient hose-reel bracket accepts swivel or stationary reels for ease in hose maneuverability and storage

2 HP, 115V, 1PH electric motor is drip proof and comes with thermal overload protection and manual reset

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

Rust-proof, non-contaminating polyethylene fuel tank includes fuel gauge in cap

37-ft. power cord with safety **Ground Fault Circuit Interrupter** (GFCI breaker)

Stainless-steel coil skin provides extra durability to withstand the elements

Pressure relief valve protects the machine and user from thermal expansion

Upright, oil-fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Heavy-duty trigger gun and wand with insulated cool grips

Built-in wand and hose holder provides convenient storage



Simple, easy-to-use control panel includes adjustable temperature control plus heavy-duty heater and pump motor switches

50-ft. length of high-pressure hose for easy maneuverability around a large cleaning area

Semi-pneumatic tires eliminate the risk of flats

FEATURES

- 2.2 GPM @ 1300 PSI / Direct-Drive Pump
- Oil-Fired Heater
- 7-Yr Pump Warranty
- ETL-Certified to UL-1776 safety standards



Hotsty duplex, direct-drive, positive-displacement pump carries seven-year crankcase and lifetime manifold warranties. Features NESTechnology with U-Seals for longer life.

Adjustable, spray-angle nozzle with 0° to 80° spray patterns adjusts easily under high pressure

Nothing Cleans Like a Hotsty!

555SS Hot Water **ELECTRIC** Model

■ Oil-Fired Heater ■ 2.2 GPM @ 1300 PSI ■ Hotsy Duplex Pump with 7-yr warranty ■ Portability standard ■ ETL-Certified for safety

Designed for tough, industrial cleaning.

SPECIFICATIONS

DIRECT DRIVE

MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
555SS	2.2	1300	2	115/1	20	Oil	214,300	Duplex-HHC165L.1	Direct	Std	50'	370

Dimensions: 42"l x 29"w x 49"h



Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with specially formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs. Over 80% of Hotsy's distributors have been supporting Hotsy systems for more than 20 years.

This seasoned network of local service professionals will ensure you get the safest, most effective and most efficient cleaning solution to your specific cleaning need.



OPTIONS

- 8" Oil-Fired Draft Dampener

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Distributed by:

MOTA Industrial Services, LLC

106 South Lake Court, Lexington, SC 29073

Tel: 803-356-4777 ♦ Fax: 803-356-4737

www.motaindustrial.com

hotsy *Nothing Cleans Like a Hotsy!*



NOTE: We are constantly improving and updating our products. Consequently, pictures, features and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within $\pm 5\%$ of listed specifications.