

# 13,000 & 14,000-Watt Gasoline

*Designed for the contractor, this generator is built to withstand even the most demanding applications. With a reputation for performance it is a virtual powerhouse with the added benefit of being portable enough to easily move from jobsite to jobsite.*

## Engine

- Low-oil shutdown engine with electric start (battery included)
- Idle control

## Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings

## Frame

- Reinforced 1¼-inch powder coated steel tube frame with center balanced lifting hook
- Solid steel threaded axles
- Four pneumatic tires with tubes and locking tire brake

## Components

- Large low-tone mufflers to reduce noise to lowest level possible
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Easy-to-read fuel gauge
- Voltmeter/hour meter
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- Heavy-duty industrial air cleaners hold up under extreme conditions

## Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

## Warranties




GEN-14000-1MHE

| Model Number            | GEN-13000-1MSE*  | GEN-14000-1MHE^  |
|-------------------------|--|--|
| Max. AC Output          | 13,000 watts   | 14,000 watts   |
| Rated AC Output         | 11,500 watts   | 12,000 watts   |
| Displacement/Engine     | 650cc Subaru OHV   | 688cc Honda OHV  |
| Frequency/Voltage       | 60Hz/120V/240V   | 60Hz/120V/240V   |
| Max. Amps (120V/240V)   | 108.3/54.2   | 116.7/58.3   |
| Cont. Amps (120V/240V)  | 95.8/47.9  | 100.0/50.0   |
| Receptacles             | (2) 120V, 20A GFCI duplex<br>120V, 30A twist lock<br>120V/240V, 30A twist lock<br>120V/240V, 50A   | (2) 120V, 20A GFCI duplex<br>120V, 30A twist lock<br>120V/240V, 30A twist lock<br>120V/240V, 50A   |
| Main Circuit Breakers   | (2) 20A toggle circuit breaker, single pole<br>30A toggle circuit breaker, single pole<br>30A toggle circuit breaker, double pole<br>50A toggle circuit breaker, double pole | (2) 20A toggle circuit breaker, single pole<br>30A toggle circuit breaker, single pole<br>30A toggle circuit breaker, double pole<br>50A toggle circuit breaker, double pole |
| Rated Speed             | 3600 RPM   | 3600 RPM   |
| Decibel Rating          | 77.5   | 77.5   |
| Fuel Capacity           | 13.2 gallons   | 13.2 gallons   |
| Run Time (at full load) | 8.8 hours  | 8.0 hours  |
| Dimensions (LxWxH)      | 31.5in.x30.5in.x37.5in.  | 31.5in.x30.5in.x37.5in.  |
| Ship Wt.                | 573 lbs.   | 568 lbs.   |
| Net Wt.                 | 513 lbs.   | 508 lbs.   |

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

\*EPA compliant in 49 states. Not to be sold in California.


^Carb compliant in all 50 states. Can be sold in California.



GFCI 5-20R



NEMA L14-30R  
125/250V



NEMA 14-50R  
50A



NEMA L5-30R  
125 VAC



GX-0005 option  
CS6369A  
50A twist lock  
receptacle



CSA  
CERTIFIED

## ACCESSORIES & OPTIONS

| Part Number | Description  | Fits Models |
|-------------|--|-------------|
| 32-0915     | RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators    | All models  |
| GX-0003     | Skid feet - For stationary applications  | All models  |
| GX-0005     | 50-amp twist lock receptacle - Marine receptacle for routine marine applications             | All models  |
| TX-1304-W   | Puncture-proof tires - Tires are flat-free, maintenance-free, 13-inch, white hub, four tires | All models  |