

AIR COMPRESSOR/GENERATORS

Two Stage Gasoline

30-Gallon

Power this mighty unit with either a Honda, Kohler or Subaru engine, include a cast iron two-stage compressor and an industrial 3500 or 4000-watt generator and you'll have enough electrical power and the ability to power air tools in your shop or in the most remote locations. The 30-gallon storage tank gives you enough air capacity for extra productivity. Whatever your needs, this all-in-one piece of equipment is well worth the investment.



AG2-SR14-30M



NEMA 5-15R



NEMA L6-20R
20A 250V
AX-0066 option



AX-0066 230V outlet option - adds 230V outlet to air compressor/generator

Compressor Pump

- Quality cast iron two stage compressor with venting system for reduced crankcase temperature and pressure
- Splash lubricated cast iron crankcase to extend the hours of performance
- Cast iron head for heat dissipation
- Large canister intake filter
- Durable stainless-steel braided discharge hose for longer life

Engine

- Honda OHV, Kohler OHV or Subaru OHC engine

Generator

- Industrial 3500 or 4000-watt generator with four NEMA 5-15R receptacles
- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings

Frame

- Powder coated ASME coded 30-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts

Components

- Belt tightening system pulls engine straight to ensure constant belt alignment
- Regulator and two gauges for tank and outlet pressure
- 16.5-inch fly wheel for extra cooling and longer life
- Manual drain valves for proper maintenance
- Quality pilot valve unloader

Warranties

2 YEAR LIMITED PUMP EXCHANGE WARRANTY See page 55 for more information	2 YEAR LIMITED ALTERNATOR WARRANTY	3 YEAR LIMITED HONDA ENGINE WARRANTY	3 YEAR LIMITED KOHLER ENGINE WARRANTY	3 YEAR LIMITED SUBARU ENGINE WARRANTY
---	--	--	---	---

NEW KOHLER ENGINE MODEL

Model Number	Alternator Wattage			Receptacles	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
	CFM @ 100 PSI	CFM @ 175 PSI	Max. Output					
AG2-SH13-30M	16.3	15.7	3500 watts	(4) NEMA 5-15R	389cc Honda OHV	40in.x24.5in.x45in.	500 lbs.	435 lbs.
AG2-SK14-30M	16.3	15.7	4000 watts	(4) NEMA 5-15R	429cc Kohler OHV	40in.x24.5in.x45in.	500 lbs.	435 lbs.
AG2-SR14-30M	16.3	15.7	4000 watts	(4) NEMA 5-15R	404cc Subaru OHC	40in.x24.5in.x45in.	500 lbs.	435 lbs.

ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
70-0358	Engine oil drain - 14-inch flexible drain hose to make oil changes cleaner and easier	Honda & Kohler models
70-0380	Engine oil drain - 14-inch flexible drain hose to make oil changes cleaner and easier	AG2-SR14-30M
854-0093	Service truck mount kit (recommended for models that are mounted in service truck applications) - Includes four rubber isolators to reduce wear	All models
AX-0019	Electric start (battery and cables not included) - For easy starting	AG2-SH13-30M
AX-0062	Electric start (battery and cables not included) - For easy starting	AG2-SR14-30M
AX-0063	Lifting hook - For easier portability	All models
AX-0064	Electric start (battery box included) - For easy starting	AG2-SH13-30M
AX-0065	Electric start (battery box included) - For easy starting	AG2-SR14-30M
AX-0066	230V outlet - Adds 230V outlet to model	All models
AX-0068	Idle down - When activated it automatically throttles down engine to conserve fuel	AG2-SH13-30M
AX-0069	Idle down - When activated it automatically throttles down engine to conserve fuel	AG2-SR14-30M