

# Two Stage Gasoline

## 20-Gallon

*If you're in the market for power then this air compressor will meet all your needs. Strong and durable, quick and efficient, it is built of cast iron and stainless-steel and can store ample pressure with its powder coated ASME 20-gallon receiver tank. Portable or stationary, this unit will deliver.*



AM2-PH09-20M



AM2-SH09-20M shown with optional electric start (AX-0015)

### All Models Feature Compressor Pump

- Quality cast iron two stage compressor with venting system for reduced crankcase temperature and pressure
- Splash lubricated cast iron crankcase to extend the hours of performance
- Cast iron head for heat dissipation
- Stainless-steel braided discharge hose
- Large canister intake filter

### Engine

- Industrial Honda OHV (Electric start optional)
- Pneumatic idle control to conserve fuel
- Engine oil drain

### Frame

- Powder coated ASME coded 20-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts

### Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- Belt tightening system pulls engine straight to ensure constant belt alignment
- 16.5-inch fly wheel for extra cooling and longer life
- Quality pilot valve unloader

### AM2-PH09-20M Model Additional Features

#### Frame

- Convenient lifting handles
- Two pneumatic tires with tubes and steel hubs

### Warranties for All Models

**2** YEAR LIMITED  
PUMP EXCHANGE WARRANTY  
See page 55 for more information

**3** YEAR LIMITED  
HONDA ENGINE WARRANTY

### PORTABLE MODEL

Model Number	CFM @ PSI	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM2-PH09-20M	17.2 @ 175	270cc Honda OHV	46in.x26in.x39.5in.	356 lbs.	306 lbs.

### STATIONARY MODEL

Model Number	CFM @ PSI	Displacement/Engine	Dimensions (LxWxH)	Bolt Down (LxW)	Ship Wt.	Net Wt.
AM2-SH09-20M	17.2 @ 175	270cc Honda OHV	37in.x18in.x38in.	23.193in.x11in.	356 lbs.	306 lbs.

### ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
AW-0007-0196	Rear lifting handle (N/A for models with electric start options) - Allows unit to be lifted from both ends	AM2-PH09-20M
AX-0003	Manual drain metal bowl - Drains moisture from air system	All models
AX-0015	Electric start (battery and cables not included) - For easy starting	AM2-SH09-20M
AX-0017	Electric start (battery and cables included) - For easy starting	All models
Consult Factory	Cable throttle control - Automatically throttles down engine to conserve fuel	All models
TX-1302-W	Puncture-proof tires - Tires are flat-free, maintenance-free, 13-inch, white hub, two tires	AM2-PH09-20M