Cold Water Gasoline Belt Drive

The popular CBA Series of pressure washers features a lightweight aluminum frame, base plate and belt guard making it one of the most lightweight, yet industrial-quality models in the industry. The patented vibration isolation plate is designed to absorb vibration and noise and will reduce movement of the unit while it is running.

CBA Aluminum Series



General pumps feature an external bypass system which allows more water into the system to protect from heat build-up



Patented vibration isolation plate with four rubber isolators for reduced movement



Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- Stainless-steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Engine

- Performance-proven engine with low-oil protection

- Light, corrosion resistant aluminum frame
- 1-inch aluminum tube handles for easier pulling
- Aluminum base plate
- Two-piece belt guard for quick access to belts
- Solid 1/8-inch diameter full-length threaded axle
- Pneumatic tires with tubes for longer life
- Dual rubber isolators

Component

- Dual cogged belt drive system for increased belt life

Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 48-inch lance with rubber grip

Warranties







Model Number	PSI	GPM	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CBA-3504-0MHB	3500	3.7	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-3504-0MRB	3500	3.7	404cc Subaru OHC	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-3504-1MHB*	3500	4.0	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-0MHB	4000	3.4	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-0MRB	4000	3.4	404cc Subaru OHC	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-1MHB*	4000	3.5	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.

^{*}Model comes standard with external bypass system and General pump.

ACCESSORIES & OPTIONS

NOCEOUTIES & OF HORS							
Part Number	Description	Fits Models					
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models					
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models					
	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models					
CX-0082	External bypass system - Allows more water into the system to protect from heat build-up; attaches to the pump	All models except 1MHBs					
TX-1302-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, two tires	All models					