Cold Water Gasoline Belt Drive

JCW Series

Don't let the compact design of the JCW Series pressure washers fool you. This rugged belt-driven unit is built with an all-steel frame and base plate and can handle even the toughest environments. The JCW Series delivers cleaning of up to 4000-PSI and every model features an AR pump with a limited 7 year warranty.



Pump

- Stainless-steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Engine

- Performance-proven engine with low-oil protection

Frame

- 11/4-inch powder coated steel tube handles (1-inch on 2400 to 2700-PSI models)
- Powder coated steel base plate with welded reinforcement for reduced vibration
- Two-piece belt guard with 1/4-turn release for quick access to belts
- Convenient gun/wand holder and hose wrap
- Solid steel threaded axle
- Pneumatic tires with tubes for longer life
- Dual rubber isolators

Component

- Dual cogged belt drive system for increased belt life

Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 & 4000-PSI models)

Warranties







Model Number	PSI	GPM	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JCW-2403-0MHB	2400	2.8	196cc Honda OHV	37.5in.x22in.x25in.	171 lbs.	121 lbs.
JCW-2403-0MRB	2400	2.8	211cc Subaru OHC	37.5in.x22in.x25in.	171 lbs.	121 lbs.
JCW-2703-0MHB	2700	2.4	196cc Honda OHV	37.5in.x22in.x25in.	171 lbs.	121 lbs.
JCW-2703-0MRB	2700	2.4	211cc Subaru OHC	37.5in.x22in.x25in.	171 lbs.	121 lbs.
JCW-3504-0MHB	3500	3.7	389cc Honda OHV	39.5in.x28.5in.x26in.	245 lbs.	191 lbs.
JCW-3504-0MRB	3500	3.7	404cc Subaru OHC	39.5in.x28.5in.x26in.	245 lbs.	191 lbs.
JCW-4004-1MHB	4000	3.4	389cc Honda OHV	39.5in.x28.5in.x26in.	249 lbs.	195 lbs.
JCW-4004-1MRB	4000	3.4	404cc Subaru OHC	39.5in.x28.5in.x26in.	249 lbs.	195 lbs.

ACCESSORIES & OPTIONS

AUGESSUNIES & UTTIONS							
Part Number	Description	Fits Models					
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models					
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models					
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models					
CX-0082	External bypass system - Allows more water into the system to protect from heat build-up; attaches to the pump	All models					
CX-0085	External bypass system - Allows more water into the system to protect from heat build-up; attaches to the base plate	All models					
TX-1002-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 10-inch, white hub, two tires	2400 to 2700-PSI models					
TX-1302-W	Puncture-proof tires - Tires are flat-free and maintenance-free. 13-inch, white hub, two tires	3500 to 4000-PSI models					

