

# Cold Water Gasoline Direct Drive

The JP Series features a 1-inch steel extended handle design for excellent balance and mobility. Equipped with either a powerful Honda engine or performance proven Subaru engine this model has great cleaning power.

## JP Series



JP-3003-0MRB

### Pump

- Direct drive triplex piston AR pump with ceramic plungers
- Stainless-steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- In-line water strainer

### Engine

- Performance-proven engine with low-oil protection

### Frame

- 1-inch powder coated steel tube handles for easier pulling
- Powder coated and welded steel base plate
- Convenient gun/wand holder and hose wrap
- Solid steel axle (threaded on 3500 & 4000-PSI models)
- Pneumatic tires with tubes for longer life
- Dual rubber isolators

### Unit Includes

- Quick connect nozzles (0°, 15° and 25°)
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch lance on 3500 & 4000-PSI models)

### Warranties



Model Number	PSI	GPM	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JP-2403-0MHB	2400	2.4	196cc Honda OHV	37in.x21in.x24.5in.	100 lbs.	75 lbs.
JP-2403-0MRB	2400	2.4	211cc Subaru OHC	37in.x21in.x24.5in.	100 lbs.	75 lbs.
JP-2703-0MHB	2700	2.4	196cc Honda OHV	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-2703-0MRB	2700	2.4	211cc Subaru OHC	37in.x21in.x24.5in.	110 lbs.	85 lbs.
JP-3003-0MHB	3000	3.0	270cc Honda OHV	40in.x22.5in.x24.5in.	180 lbs.	130 lbs.
JP-3003-0MRB	3000	3.0	265cc Subaru OHC	40in.x22.5in.x24.5in.	180 lbs.	130 lbs.
JP-3504-0MHB	3500	3.5	389cc Honda OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-3504-0MRB	3500	3.5	404cc Subaru OHC	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-4004-1MHB	4000	3.5	389cc Honda OHV	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.
JP-4004-1MRB	4000	3.5	404cc Subaru OHC	40in.x22.5in.x24.5in.	192 lbs.	142 lbs.

### ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
50-0161	<b>High pressure detergent injection</b> - High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-8400-0021	<b>Low pressure detergent injection</b> - Allows the user to apply the recommended detergents	All models
CX-0005	<b>Insulated dual lance</b> - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models
CX-0083	<b>External bypass</b> - Allows more water into the system to protect from heat build-up	2400 to 2700-PSI models
CX-0084	<b>External bypass</b> - Allows more water into the system to protect from heat build-up	3000 to 4000-PSI models
TX-1002-W	<b>Puncture-proof tires</b> - Tires are flat-free and maintenance-free, 10-inch, white hub, two tires	All models